




AL



LINGATEC SOLUÇÃO EM MOVIMENTAÇÃO DE CARGAS LTDA
 Rua Danilo Valbuza, 600 - Laranjeiras - CAIEIRAS/SP - CEP: 07747-300
 11-4441-5420 - vendas@lingatec.com.br - www.lingatec.com.br

Green Pin® Lifting Eye GR8

Grade 8 lifting eye

- **Material:** alloy steel, grade 8, quenched and tempered
- **Safety factor:** MBL equals 5 x WLL
- **Standard:** EN1677-1 and ASME B30.26
- **Finish:** painted red or white
- **Temperature range:** -40 °C up to +200 °C
- **Certification:** 2.1 2.2 3.1 MTC® MPI® CE IIA
- **Article code:** scan QR code to see article codes

Scan for
additional
product
details



working load limit	diameter thread	diameter base	diameter eye outside	diameter eye inside	length	thickness base	diameter	weight each
t	a mm	b mm	c mm	d mm	e mm	f mm	g mm	kg
0.2	M6 x 1.00	20	34	20	20	17	7	0.05
0.4	M8 x 1.25	20	34	20	24	17	7	0.06
0.7	M10 x 1.50	20	38	22	30	19	8	0.08
1	M12 x 1.75	25	47	27	36	23	10	0.14
1.2	M14 x 2.00	30	57	30	40	27	14	0.25
1.5	M16 x 2.00	36	63	35	55	31	14	0.39
2	M18 x 2.50	36	63	35	55	31	14	0.40
2.5	M20 x 2.50	40	72	40	59	34	16	0.58
3	M22 x 2.50	42	82	45	66	38	19	0.77
4	M24 x 3.00	55	95	55	84	40	20	1.19
5	M27 x 3.00	55	95	55	84	40	20	1.18
6	M30 x 3.50	60	108	60	99	51	24	1.87
7	M33 x 3.50	60	108	60	99	51	24	1.96
8	M36 x 4.00	65	118	68	117	48	25	2.44
9	M39 x 4.00	65	118	68	117	48	25	2.59
10	M42 x 4.50	70	142	80	135	61	31	4.14
15	M45 x 4.50	70	142	80	135	61	31	4.15
18	M48 x 5.00	95	181	97	150	69	42	8.22
20	M52 x 5.00	95	181	97	150	69	42	8.55
25	M56 x 5.50	95	181	97	150	69	42	8.85
30	M60 x 5.50	95	181	97	150	69	42	9.16
36	M64 x 6.00	95	181	97	150	69	42	9.55

CAD INFO