




ALUNC



LINGATEC SOLUÇÃO EM MOVIMENTAÇÃO DE CARGAS LTDA
 Rua Danilo Valbuza, 600 - Laranjeiras - CAIEIRAS/SP - CEP: 07747-300
 11-4441-5420 - vendas@lingatec.com.br - www.lingatec.com.br

Green Pin® Lifting Eye UNC GR8

Grade 8 lifting eye UNC

- **Material:** alloy steel, grade 8, quenched and tempered
- **Safety factor:** MBL equals 5 x WLL
- **Standard:** EN1677-1 and ASME B30.26
- **Finish:** painted red or white
- **Temperature range:** -40 °C up to +200 °C
- **Certification:** 2.1 2.2 3.1 MTC[®] MPI[®] CE IIA
- **Article code:** scan QR code to see article codes

Scan for
additional
product
details



working load limit	diameter thread	diameter base	diameter eye outside	diameter eye inside	length	thickness base	diameter	weight each
t	a mm	b mm	c mm	d mm	e mm	f mm	g mm	kg
0.2	1/4 - 20UNC	20	34	20	20	17	7	0.05
0.7	3/8 - 16UNC	20	38	22	30	19	8	0.08
1	1/2 - 13UNC	25	47	26	36	23	10	0.14
1.5	5/8 - 11UNC	36	65	35	53	30	14	0.38
2.5	3/4 - 10UNC	40	73	39	58	34	16	0.55
3	7/8 - 9UNC	42	82	44	64	38	19	0.81
4	1 - 8UNC	55	95	54	84	40	20	1.14
5	1 1/8 - 7UNC	55	95	54	84	40	20	1.21
6	1 1/4 - 7UNC	60	108	59	99	49	24	1.90
8	1 1/2 - 6UNC	65	118	67	117	45	25	2.52
10	1 3/4 - 5UNC	70	142	80	135	61	31	4.26
15	2 - 4 1/2UNC	70	142	80	135	61	31	4.66
25	2 1/2 - 4UNC	95	181	97	150	69	42	9.55