




CFO



LINGATEC SOLUÇÃO EM MOVIMENTAÇÃO DE CARGAS LTDA
 Rua Danilo Valbuza, 600 - Laranjeiras - CAIEIRAS/SP - CEP: 07747-300
 11-4441-5420 - vendas@lingatec.com.br - www.lingatec.com.br

Green Pin® Foundry Hook E GR8

Grade 8 eye foundry hook

- **Material:** alloy steel, grade 8, quenched and tempered
- **Safety factor:** MBL equals 4 x WLL
- **Standard:** EN1677-1 and ASTM A952/A952M
- **Finish:** painted yellow (J), red (R) or white
- **Temperature range:** -40 °C up to +200 °C
- **Certification:** 2.1 2.2 3.1 * MTC * MPI * DGUV * CE IIB
- **Article code:** scan QR code to see article codes
- **Note:** from 8.2 t without flat part

Scan for
additional
product
details



for chain diameter	working load limit	length	diameter eye inside	width opening	thickness	width	diameter eye outside	width outside	length	thickness	weight each
mm	t	a mm	b mm	c mm	d mm	e mm	f mm	g mm	h mm	i mm	kg
6	1.12	93	19	48	17	21	38	97	124	7	0.33
7/8	2	125	25	64	22	28	50	129	165	9	0.78
10	3.2	157	34	79	27	35	65	161	208	11	1.50
13	5.4	190	44	95	35	45	84	198	254	13	3
16**	8.2	205	35	95	45	52	88	204	284	24	4.16
18/20**	12.8	235	40	111	53	55	92	228	315	25	7.80
22**	15.5	265	46	123	66	71	110	258	268	32	9.87
26**	21.6	305	54	133	65	81	120	277	420	33	13.8
32**	32.8	327	60	155	84	96	131	333	459	35	24.5

* Excluding sizes 16 mm, 18/20 mm, 22 mm, 26 mm and 32 mm

** Different design

* could be delivered with a yellow or red finish