





CO



LINGATEC SOLUÇÃO EM MOVIMENTAÇÃO DE CARGAS LTDA
 Rua Danilo Valbuza, 600 - Laranjeiras - CAIEIRAS/SP - CEP: 07747-300
 11-4441-5420 - vendas@lingatec.com.br - www.lingatec.com.br

Green Pin® Omega Link EN 1677-1 GR8

Grade 8 omega link EN 1677-1

- **Material:** alloy steel, grade 8, quenched and tempered
- **Safety factor:** MBL equals 4 x WLL
- **Standard:** EN1677-1 and ASTM A952/952M
- **Finish:** painted white*
- **Temperature range:** -40 °C up to +200 °C
- **Certification:** 2.1 2.2 3.1 MTC^a MPI^b DGUV CE IIB
- **Article code:** scan QR code to see article codes
- **Note:** specific load pins available for 5, 7 and 9 mm hoist chain on request, which can be combined with respectively GPCO6, GPCO7/8, GPCO10

Scan for
additional
product
details



for chain diameter	working load limit	width	diameter pin	width	length inside	width bow	length outside	thickness	width outside	width outside	thickness	weight each
mm	t	a mm	b mm	c mm	d mm	e mm	f mm	g mm	h mm	i mm	j mm	kg
6	1.12	14	8	7	25	20	53	13	41	28	6	0.07
7/8	2	20	9	9	34	24	71	16	55	32	9	0.20
10	3.2	19	13	12	40	31	82	17	63	42	11	0.28
13	5.4	25	16	15	51	40	106	20	84	54	14	0.64
16	8.2	32	20	19	64	48	132	25	104	68	17	1.28
18/20	12.8	38	24	23	80	59	163	30	126	82	22	2.25

CAD INFO