





CRC



LINGATEC SOLUÇÃO EM MOVIMENTAÇÃO DE CARGAS LTDA
 Rua Danilo Valbuza, 600 - Laranjeiras - CAIEIRAS/SP - CEP: 07747-300
 11-4441-5420 - vendas@lingatec.com.br - www.lingatec.com.br

Green Pin® Grab Hook CL EN 1677-1 GR8

Grade 8 clevis grab hook EN 1677-1

- **Material:** alloy steel, grade 8, quenched and tempered
- **Safety factor:** MBL equals 4 x WLL
- **Standard:** EN1677-1 and ASTM A952/A952M
- **Finish:** painted white*
- **Temperature range:** -40 °C up to +200 °C
- **Certification:** 2.1 2.2 3.1 MTC* MPI* CE IIB
- **Article code:** scan QR code to see article codes

Scan for
additional
product
details



for chain diameter	working load limit	length	width	width outside	opening	thickness	width	width outside	length outside	diameter pin	weight each
mm	t	a mm	b mm	c mm	d mm	e mm	f mm	g mm	h mm	i mm	kg
6	1.12	52	7	28	8	24	19	42	85	8	0.23
7/8	2	64	9	33	10	33	23	53	103	9	0.45
10	3.2	89	11	42	12	42	39	66	151	13	1.05
13	5.4	103	15	54	15	56	40	78	173	16	2.05
16	8.2	120	18	67	19	65	58	106	214	20	3.03

CAD INFO

* could be delivered with a yellow or red finish