





CRO



LINGATEC SOLUÇÃO EM MOVIMENTAÇÃO DE CARGAS LTDA
 Rua Danilo Valbuza, 600 - Laranjeiras - CAIEIRAS/SP - CEP: 07747-300
 11-4441-5420 - vendas@lingatec.com.br - www.lingatec.com.br

Green Pin® Grab Hook E EN 1677-1 GR8

Grade 8 eye grab hook EN 1677-1

- **Material:** alloy steel, grade 8, quenched and tempered
- **Safety factor:** MBL equals 4 x WLL
- **Standard:** EN1677-1 and ASTM A952/A952M
- **Finish:** painted white*
- **Temperature range:** -40 °C up to +200 °C
- **Certification:** 2.1 2.2 3.1 ** MTC^a MPI^b ** DGUV ** CE IIB
- **Article code:** scan QR code to see article codes

Scan for
additional
product
details



for chain diameter	working load limit	length	inside length eye	inside width eye	opening	thickness	width	width outside	length outside	width	thickness	weight each
mm	t	a mm	b mm	c mm	d mm	e mm	f mm	g mm	h mm	i mm	j mm	kg
6	1.12	41	24	23	8	24	20	42	94	9	6	0.24
7/8	2	53	27	27	10	33	23	53	115	10	8	0.33
10	3.2	67	38	36	12	42	39	66	158	14	10	0.91
13	5.4	84	42	42	15	56	40	87	186	16	12	2.02
16	8.2	104	53	52	19	65	58	106	236	17	16	2.49
20	12.8	130	37	37	22	75	48	128	241	26	26	6.28
22	15.5	120	44	44	25	77	57	132	247	26	26	6.09
26***	21.6	158	46	46	30	100	82	177	320	32	32	14.7
32***	32.8	210	57	57	38	91	88	215	395	39	39	18

** Excluding sizes 20 mm, 22 mm, 26 mm and 32 mm

*** Different design