



LINGATEC SOLUÇÃO EM MOVIMENTAÇÃO DE CARGAS LTDA
 Rua Danilo Valbuza, 600 - Laranjeiras - CAIEIRAS/SP - CEP: 07747-300
 11-4441-5420 - vendas@lingatec.com.br - www.lingatec.com.br



Green Pin® Sling Hook CL EN 1677-2 GR8

Grade 8 clevis sling hook EN 1677-2




- **Material:** alloy steel, grade 8, quenched and tempered
- **Safety factor:** MBL equals 4 x WLL
- **Standard:** EN1677-2 and ASTM A952/A952M
- **Finish:** painted white*
- **Temperature range:** -40 °C up to +200 °C
- **Certification:** 2.1 2.2 3.1 MTC^a MPI^b DGVV CE IIB
- **Article code:** scan QR code to see article codes
- **Note:** specific load pins available for 5, 7 and 9 mm hoist chain on request, which can be combined with respectively GPCSC6, GPCSC7/8, GPCSC10

Scan for
additional
product
details



CSC



for chain diameter	working load limit	length	width	width opening	thickness	width	width outside	width outside	length outside	diameter pin	weight each
mm	t	a mm	b mm	c mm	d mm	e mm	f mm	g mm	h mm	i mm	kg
6	1.12	74	7	26	15	20	28	72	108	8	0.29
7/8	2	95	9	30	20	24	32	87	136	9	0.58
10	3.2	113	12	33	24	29	42	106	164	13	1.08
13	5.4	139	15	37	32	39	54	133	208	16	2.12
16	8.2	162	19	44	40	44	68	165	240	20	3.67
18/20	12.8	199	23	61	49	62	82	208	305	24	7.32
22	15.5	239	25	75	54	65	97	242	350	28	10.7

* could be delivered with a yellow or red finish