



LINGATEC SOLUÇÃO EM MOVIMENTAÇÃO DE CARGAS LTDA
 Rua Danilo Valbuza, 600 - Laranjeiras - CAIEIRAS/SP - CEP: 07747-300
 11-4441-5420 - vendas@lingatec.com.br - www.lingatec.com.br



Green Pin® Sling Hook SE EN 1677-2 GR8

Grade 8 swivel sling hook EN 1677-2

- **Material:** alloy steel, grade 8, quenched and tempered
- **Safety factor:** MBL equals 4 x WLL
- **Standard:** EN1677-2 and ASTM A952/A952M
- **Finish:** painted white*
- **Temperature range:** -40 °C up to +200 °C

• **Certification:** 2.1 2.2 3.1 MTC^a MPI^b DGVV CE IIB


• **Article code:** scan QR code to see article codes

• **Note:** equipped with thrust needle roller bearing to enable rotation under load

Scan for
additional
product
details



CSE



for chain diameter	working load limit	length	length inside	width inside	width opening	thickness	width	width outside	length outside	diameter	thickness	weight each
mm	t	a mm	b mm	c mm	d mm	e mm	f mm	g mm	h mm	i mm	j mm	kg
5/6	1.12	100	33	32	26	15	20	72	164	12	6	0.54
7/8	2	126	40	37	30	20	25	87	204	14	8	1
10	3.2	158	47	48	33	24	29	106	250	16	11	1.90
13	5.4	189	59	58	37	32	39	133	308	21	14	3.40
16	8.2	221	67	73	44	40	44	165	356	25	17	6.35
18/20	12.8	263	87	82	61	49	62	209	437	25	21	10.4

* could be delivered with a yellow or red finish