




CSECA



LINGATEC SOLUÇÃO EM MOVIMENTAÇÃO DE CARGAS LTDA
 Rua Danilo Valbuza, 600 - Laranjeiras - CAIEIRAS/SP - CEP: 07747-300
 11-4441-5420 - vendas@lingatec.com.br - www.lingatec.com.br

Green Pin® Sling Hook SCL EN 1677-2 GR8

Grade 8 swivel sling hook with clevis EN 1677-2

- **Material:** alloy steel, grade 8, quenched and tempered
- **Safety factor:** MBL equals 4 x WLL
- **Standard:** EN1677-2 and ASTM A952/A952M
- **Finish:** painted yellow (J), red (R) or white
- **Temperature range:** -40 °C up to +200 °C
- **Certification:** 2.1 2.2 3.1 MTC^a MPI^b DGVV CE IIB
- **Article code:** scan QR code to see article codes
- **Note:** specific load pins available for 5, 7 and 9 mm hoist chain on request, which can be combined with respectively GPCSECA6, GPCSECA7/8, GPCSECA10 equipped with thrust needle roller bearing to enable rotation under load

Scan for
additional
product
details



for chain diameter	working load limit	length	width	width opening	thickness	width	width outside	width outside	length	diameter pin	weight each
mm	t	a mm	b mm	c mm	d mm	e mm	f mm	g mm	h mm	i mm	kg
6	1.12	126	7	26	15	20	56	72	159	8	0.56
7/8	2	154	9	30	20	25	65	87	196	9	0.99
10	3.2	190	12	33	24	29	79	106	240	13	1.95
13	5.4	224	14	37	32	39	96	133	293	16	3.54
16	8.2	270	18	44	40	44	121	165	350	20	6.61

CAD INFO

* could be delivered with a yellow or red finish