



LINGATEC SOLUÇÃO EM MOVIMENTAÇÃO DE CARGAS LTDA
 Rua Danilo Valbuza, 600 - Laranjeiras - CAIEIRAS/SP - CEP: 07747-300
 11-4441-5420 - vendas@lingatec.com.br - www.lingatec.com.br



Green Pin® Sling Hook E EN 1677-2 GR8

Grade 8 eye sling hook EN 1677-2




- **Material:** alloy steel, grade 8, quenched and tempered
- **Safety factor:** MBL equals 4 x WLL
- **Standard:** EN1677-2 and ASTM A952/A952M
- **Finish:** painted yellow (J), red (R) or white
- **Temperature range:** -40 °C up to +200 °C
- **Certification:** 2.1 2.2 3.1 * MTC * MPI * DGUV * CE IIB
- **Article code:** scan QR code to see article codes
- **Note:** from 8.2 t without flat part. For use of this component in a wire rope sling the safety factor must be 5 : 1, see the table on page 84

Scan for
additional
product
details



CSO



for chain diameter	working load limit	length	diameter inside eye	width opening	thickness	width	diameter eye outside	width outside	length outside	width	thickness	weight each
mm	t	a mm	b mm	c mm	d mm	e mm	f mm	g mm	h mm	i mm	j mm	kg
5/6	1.12	86	23	26	15	19	43	72	114	10	6	0.28
7/8	2	103	26	30	20	24	51	87	139	12	8	0.56
10	3.2	129	36	33	24	28	65	106	171	15	10	1.08
13	5.4	152	41	37	32	39	77	133	209	18	12	1.90
16	8.2	191	52	43	40	43	94	165	255	21	17	3.50
18/20	12.8	237	61	61	49	61	115	208	326	28	21	7.04
22	15.5	280	72	75	54	64	132	242	375	30	23	9.95
26**	21.6	251	48	73	55	86	111	236	363	32	32	14.1
32**	32.8	292	58	87	67	104	139	286	435	39	39	21.7

* Excluding sizes 26 mm and 32 mm

** Different design