



LINGATEC SOLUÇÃO EM MOVIMENTAÇÃO DE CARGAS LTDA
Rua Danilo Valbuza, 600 - Laranjeiras - CAIEIRAS/SP - CEP: 07747-300
11-4441-5420 - vendas@lingatec.com.br - www.lingatec.com.br



Green Pin® Eye Nut GR8

Grade 8 eye nut





- **Material:** alloy steel, grade 8, quenched and tempered
- **Safety factor:** MBL equals 5 x WLL
- **Standard:** EN1677-1 and ASME B30.26
- **Finish:** painted white
- **Temperature range:** -40 °C up to +200 °C
- **Certification:** 2.1 2.2 3.1 MTC^a MPI^b CE IIA
- **Article code:** scan QR code to see article codes

Scan for
additional
product
details



EL



working load limit	diameter thread	diameter base	width	width inside	thickness base	length inside	diameter	thickness	weight each
t	a mm	b mm	c mm	d mm	e mm	f mm	g mm	h mm	kg
0.2	M6 x 1.00	31	51	30	14	45	11	6	0.15
0.4	M8 x 1.25	31	51	30	14	45	11	6	0.15
0.7	M10 x 1.50	31	51	30	14	45	11	6	0.15
1	M12 x 1.75	39	56	32	15	48	12	6	0.23
1.2	M14 x 2.00	39	56	32	15	48	12	6	0.23
1.5	M16 x 2.00	44	65	37	16	60	14	8	0.38
2	M18 x 2.50	44	65	37	16	60	14	9	0.38
2.5	M20 x 2.50	44	65	37	16	60	14	9	0.37
3	M22 x 2.50	52	79	49	21	75	16	11	0.63
4	M24 x 3.00	52	79	49	21	75	16	11	0.63
5	M27 x 3.00	52	79	49	21	75	16	11	0.63
6	M30 x 3.50	66	96	58	24	88	21	14	1.11
7	M33 x 3.50	66	96	58	24	88	21	14	1.11
8	M36 x 4.00	84	121	73	39	100	25	17	2.22
9	M39 x 4.00	84	121	73	39	100	25	17	2.22
10	M42 x 4.50	84	121	73	39	100	25	17	2.22
15	M45 x 4.50	90	132	82	41	122	25	22	3.27
18	M48 x 5.00	90	132	82	41	122	25	22	3.27

CAD INFO