




LINGATEC SOLUÇÃO EM MOVIMENTAÇÃO DE CARGAS LTDA
Rua Danilo Valbuza, 600 - Laranjeiras – CAIEIRAS/SP – CEP: 07747-300
11-4441-5420 - vendas@lingatec.com.br - www.lingatec.com.br





Green Pin Super® Bow Shackle FN

Grade 8 bow shackle with safety bolt and fixed nut



G-5243



- **Material:** bow and pin alloy steel, grade 8, quenched and tempered
- **Safety Factor:** MBL equals 5 x WLL
- **Standard:** ASME B30.26 and meets performance requirements of US Fed. Spec. RR-C-271 Type IVA Class 3, grade B
- **Finish:** hot dipped galvanized (150 t and upward are painted)
- **Temperature Range:** -20 °C up to +200 °C
- **Certification:** 2.1 2.2 3.1 MTC* LROS* CE IIA
- **Article code:** scan QR code to see article codes

Scan for additional product details



working load limit	diameter bow	diameter pin	diameter eye	width eye	width inside	length inside	width bow	length	length bolt	width	thickness nut	securing bolt thread	securing bolt length	torque	weight each
t	a mm	b mm	c mm	d mm	e mm	f mm	g mm	h mm	i mm	j mm	k mm	l mm	m mm	Nm	kg
3.3	13.5	16	34	13	22	51	32	90	80	59	13	M6	35	8.4	0.44
5	16	19	40	16	27	64	43	110	98	75	17	M6	40	8.4	0.79
7	19	22	46	19	31	76	51	129	115	89	19	M6	45	8.4	1.26
9.5	22	25	52	22	36	83	58	144	130	102	22	M8	50	20	1.88
12.5	25	28	59	25	43	95	68	164	150	118	25	M8	55	20	2.78
15	28	32	67	28	47	108	75	186	166	131	27	M10	60	39	3.87
18	32	35	73	32	51	115	83	201	184	147	30	M10	65	39	5.26
21	35	38	79	35	57	133	92	227	197	162	33	M10	70	39	6.94
30	38	42	88	38	60	146	99	249	202	175	19	M8	75	20	8.79
40	45	50	104	45	74	178	126	300	243	216	23	M8	90	20	15
55	57	57	119	57	83	197	138	342	283	252	26	M10	100	39	22
85	70	70	145	70	105	260	180	438	339	320	32	M12	120	68	42
120	83	83	164	83	127	330	190	537	397	356	39	M12	140	68	70
150*	95	95	204	95	147	400	238	644	453	428	50	M12	150	68	112
175*	105	108	235	105	169	410	275	686	496	485	50	M12	160	68	160

- * For shackles WLL 150 t and WLL 175 t available with and without LROS
- * With round headed bolt