





G-6411



LINGATEC SOLUÇÃO EM MOVIMENTAÇÃO DE CARGAS LTDA
 Rua Danilo Valbuza, 600 - Laranjeiras - CAIEIRAS/SP - CEP: 07747-300
 11-4441-5420 - vendas@lingatec.com.br - www.lingatec.com.br

Green Pin® Closed Spelter Socket

- **Material:** high tensile steel, quenched and tempered
- **Finish:** hot dipped galvanized
- **Temperature Range:** -20 °C up to +200 °C
- **Certification:** 2.1 2.2 3.1 CE IIA
- **Article code:** scan QR code to see article codes

Scan for
additional
product
details



number	minimum breaking load	diameter wire rope	length	width	width inside bow	length inside bow	thickness bow	thickness bow	opening	weight each
	t	mm	a mm	b mm	c mm	d mm	e mm	f mm	g mm	kg
296	8	6 - 7	101	37	22	40	11	13	9	0.27
297	12	8 - 10	119	43	25	48	14	17.5	12	0.43
298	20	11 - 13	140	52	30	58	18	23.5	15	0.76
299	25	14 - 16	162	68	37	66	21	26	17.5	1.52
200	45	18 - 19	194	76	42	78	27	32	21.5	2.31
201	70	20 - 22	224	92	47	90	33	38	24	4.31
204	85	23 - 26	253	104	57	103	36	44	28	6.03
207	105	27 - 30	282	114	63	116	39	51	32	7.99
212	136	31 - 36	312	127	70	130	43	57	38	10.9
215	150	37 - 39	358	136	79	155	51	63	41	13.8
217	170	40 - 42	390	146	83	171	54	70	44	17.4
219	225	43 - 48	443	171	93	198	55	76	51	26.9
222	280	49 - 54	502	193	100	224	62	82	57	38.8
224	360	55 - 60	548	216	112	247	73	92	63	54.7
226	425	61 - 68	597	241	140	270	79	102	73	70.8
227	460	69 - 75	644	273	159	286	79	124	79	102
228	560	76 - 80	686	292	171	298	83	133	86	123
229	625	81 - 86	743	311	184	311	102	146	92	152
230	720	87 - 93	788	330	197	330	102	159	99	178
231	875	94 - 102	845	362	216	356	108	178	108	233
233	1200	108 - 115	1000	405	235	425	125	190	125	329
240	1300	120 - 130	1150	450	260	525	125	200	143	453

CAD