



LINGATEC SOLUÇÃO EM MOVIMENTAÇÃO DE CARGAS LTDA
Rua Danilo Valbuza, 600 - Laranjeiras - CAIEIRAS/SP - CEP: 07747-300
11-4441-5420 - vendas@lingatec.com.br - www.lingatec.com.br



Green Pin® EE Swivel


Swivel with eye-eye end-fitting

- **Material:** high tensile steel, quenched and tempered
- **Safety factor:** MBL equals 5 x WLL
- **Standard:** US Federal Spec. RR-C-271, Type VII, Class 2
- **Finish:** hot dipped galvanized
- **Certification:** 2.1 2.2 CE IIA
- **Article code:** scan QR code to see article codes
- **Note:** for WLL 8.2 t and 20.5 t swivels both eye parts are equipped with a nut

Scan for
additional
product
details



G-7713



working load limit	diameter	length outside	width outside	length inside	width inside	length inside	length	weight each
t	a mm	b mm	c mm	d mm	e mm	f mm	g mm	kg
0.4	6	87	32	18	19	27	75	0.10
0.6	8	107	41	21	25	32	91	0.18
1.12	10	131	51	24	32	38	111	0.30
1.63	13	164	64	33	38	51	138	0.60
2.4	16	198	76	40	45	61	166	1
3.3	19	221	89	45	51	67	183	1.79
4.54	22	257	102	53	57	78	213	2.55
5.7	25	298	114	59	64	86	248	4.06
8.2	32	357	143	68	80	68	293	8.48
20.5	38	541	198	110	122	110	465	25.7