



LINGATEC SOLUÇÃO EM MOVIMENTAÇÃO DE CARGAS LTDA
Rua Danilo Valbuza, 600 - Laranjeiras - CAIEIRAS/SP - CEP: 07747-300
11-4441-5420 - vendas@lingatec.com.br - www.lingatec.com.br



Green Pin® Shortening Clutch EN 1677-1 GR8


Grade 8 shortening clutch EN 1677-1

- **Material:** alloy steel, grade 8, quenched and tempered
- **Safety factor:** MBL equals 4 x WLL
- **Standard:** EN 1677-1, DIN 5692 and ASTM A952/A952M
- **Finish:** painted white*
- **Temperature range:** -40 °C up to +200 °C
- **Certification:** 2.1 2.2 3.1 MTC^a MPI^b DGUV CE IIB
- **Article code:** scan QR code to see article codes

Scan for
additional
product
details



GC



for chain diameter	working load limit	length	width inside	length	width outside	width	diameter pin	weight each
mm	t	a mm	b mm	c mm	d mm	e mm	f mm	kg
6	1.12	52	23	75	42	7	8	0.23
7/8	2	67	30	94	50	9	9	0.44
10	3.2	83	38	116	63	11	13	0.87
13	5.4	104	49	149	79	14	16	1.76
16	8.2	127	60	184	99	18	20	3.20
18/20	12.8	154	75	215	124	22	24	5.78

CAD INFO