





GH



LINGATEC SOLUÇÃO EM MOVIMENTAÇÃO DE CARGAS LTDA
 Rua Danilo Valbuza, 600 - Laranjeiras - CAIEIRAS/SP - CEP: 07747-300
 11-4441-5420 - vendas@lingatec.com.br - www.lingatec.com.br

Green Pin® Excavator Hook GR8

Grade 8 excavator hook

- **Material:** alloy steel, grade 8, quenched and tempered
- **Safety factor:** MBL equals 4 x WLL
- **Standard:** EN1677-1
- **Finish:** painted white*
- **Temperature range:** -40 °C up to +200 °C
- **Certification:** 2.1 2.2 3.1 MTC^a MPI^b CE II A
- **Article code:** scan QR code to see article codes
- **Note:** welding must be done in accordance with DIN 5817 resp. 15429, by a qualified welder according to EN 287-1

Scan for
additional
product
details



working load limit	width	length	width opening	thickness	width	length	width	width	weight each
t	a mm	b mm	c mm	d mm	e mm	f mm	g mm	h mm	kg
1	72	78	25	19	28	108	31	26	0.52
2	178	197	60	46	61	227	50	66	0.75
3	185	223	65	60	70	251	55	80	1.15
4	91	83	33	20	28	113	31	34	1.66
5	105	105	33	26	32	128	31	34	2.50
8	121	130	35	27	36	148	40	38	3.32
10	138	149	43	28	45	166	40	44	6.44
15	145	148	43	41	52	173	40	51	9.70

CAD INFO