




GKO



LINGATEC SOLUÇÃO EM MOVIMENTAÇÃO DE CARGAS LTDA
 Rua Danilo Valbuza, 600 - Laranjeiras - CAIEIRAS/SP - CEP: 07747-300
 11-4441-5420 - vendas@lingatec.com.br - www.lingatec.com.br

Green Pin® Self Locking Hook E GR8

Grade 8 eye self locking hook

- **Material:** alloy steel, grade 8, quenched and tempered
- **Safety factor:** MBL equals 4 x WLL
- **Finish:** painted yellow (J), red (R) or white
- **Temperature range:** -40 °C up to +200 °C
- **Certification:** 2.1 2.2 MTC[®] MPI[®] CE IIB
- **Article code:** scan QR code to see article codes
- **Note:** GK hooks are more compact than XL hooks
for use of this component in a wire rope sling the safety factor must be 5 : 1,
see the table on page 84

Scan for
additional
product
details



for chain diameter	working load limit	length	diameter inside eye	width opening	thickness	width	width outside	width outside	length	width	thickness	weight each
mm	t	a mm	b mm	c mm	d mm	e mm	f mm	g mm	h mm	i mm	j mm	kg
7/8	2	112	26	32	17	24	48	75	147	11	9	0.53
10	3.2	136	31	44	24	28	60	91	179	15	10	0.96
13	5.4	174	40	48	32	33	76	111	226	18	12	1.86
16	8.2	209	50	63	37	42	93	141	273	22	16	3.49
18/20	12.8	254	61	75	44	55	116	184	337	28	20	7.33
22	15.5	288	72	90	52	61	132	205	379	30	21	9.91

CAD INFO