


MDVI



LINGATEC SOLUÇÃO EM MOVIMENTAÇÃO DE CARGAS LTDA
 Rua Danilo Valbuza, 600 - Laranjeiras - CAIEIRAS/SP - CEP: 07747-300
 11-4441-5420 - vendas@lingatec.com.br - www.lingatec.com.br

Green Pin® Dee Shackle S/S-GR5

Grade 5 stainless steel dee shackle with screw collar pin

- **Material:** AISI 316, grade 5
- **Safety factor:** MBL equals 5 x WLL
- **Finish:** polished
- **Temperature range:** -40 °C up to +200 °C
- **Certification:** 2.1 2.2 3.1 CE IIA
- **Note:** marked with GP, WLL and CE

Scan for
additional
product
details



working load limit	diameter bow	diameter pin	diameter eye	width inside	length inside	length	weight each
t	a mm	b mm	c mm	d mm	e mm	f mm	kg
0.4	8	8	16	16	32	52	0.06
0.6	10	10	19	20	40	65	0.11
0.9	12	12	24	25	48	78	0.19
1.5	13	16	31	24	52	89	0.30
2.5	16	20	38	28	64	109	0.57
3	19	22	44	32	72	124	0.90
4	22	25	50	37	74	134	1.33
6	25	30	57	40	94	163	1.98