



LINGATEC SOLUÇÃO EM MOVIMENTAÇÃO DE CARGAS LTDA
Rua Danilo Valbuza, 600 - Laranjeiras - CAIEIRAS/SP - CEP: 07747-300
11-4441-5420 - vendas@lingatec.com.br - www.lingatec.com.br



Green Pin® Round Web Sling Connecting Link GR8


Grade 8 round web sling connecting link

- **Material:** alloy steel, grade 8, quenched and tempered
- **Safety factor:** MBL equals 4 x WLL
- **Standard:** EN1677-1 and ASTM A952/952M
- **Finish:** painted white*
- **Temperature range:** -40 °C up to +200 °C
- **Certification:** 2.1 2.2 3.1 MTC^a MPI^b CE IIB
- **Article code:** scan QR code to see article codes


Scan for
additional
product
details



MJS



g



for chain diameter	working load limit	diameter	width outside	width inside	length inside	length	width inside	diameter eye	thickness	weight each
mm	t	a mm	b mm	c mm	d mm	e mm	f mm	g mm	h mm	kg
7/8	2	9	66	19	21	60	41	13	14	0.31
10	3.2	10	75	23	24	75	46	18	15	0.51
13	5.4	14	87	28	32	90	52	24	19	1.01