



LINGATEC SOLUÇÃO EM MOVIMENTAÇÃO DE CARGAS LTDA
 Rua Danilo Valbuza, 600 - Laranjeiras - CAIEIRAS/SP - CEP: 07747-300
 11-4441-5420 - vendas@lingatec.com.br - www.lingatec.com.br



Green Pin® Bow Shackle S/S-GR5


Grade 5 stainless steel bow shackle with screw collar pin

- **Material:** AISI 316, grade 5
- **Safety factor:** MBL equals 5 x WLL
- **Finish:** polished
- **Temperature range:** -40 °C up to +200 °C
- **Certification:** 2.1 2.2 3.1 CE IIA
- **Note:** marked with GP, WLL and CE

Scan for
additional
product
details



MLVI



working load limit	diameter bow	diameter pin	diameter eye	width inside	length inside	width bow	length	width	weight each
t	a mm	b mm	c mm	d mm	e mm	f mm	g mm	h mm	kg
0.4	8	8	16	16	32	24	52	40	0.06
0.6	10	10	19	20	40	30	65	50	0.12
0.9	12	12	24	25	49	36	76	60	0.20
1.5	13	16	31	24	52	35	89	59	0.32
2.5	16	20	38	28	61	43	106	75	0.58
3	19	22	44	32	72	51	124	89	0.96
4	22	25	50	37	85	58	145	102	1.46
6	25	30	57	40	95	66	164	116	2.09




Green Pin® Dee Shackle S/S-GR5

Grade 5 stainless steel dee shackle with screw collar pin

- **Material:** AISI 316, grade 5
- **Safety factor:** MBL equals 5 x WLL
- **Finish:** polished
- **Temperature range:** -40 °C up to +200 °C
- **Certification:** 2.1 2.2 3.1 CE IIA
- **Note:** marked with GP, WLL and CE



MDVI



working load limit	diameter bow	diameter pin	diameter eye	width inside	length inside	length	weight each
t	a mm	b mm	c mm	d mm	e mm	f mm	kg
0.4	8	8	16	16	32	52	0.06
0.6	10	10	19	20	40	65	0.11
0.9	12	12	24	25	48	78	0.19
1.5	13	16	31	24	52	89	0.30
2.5	16	20	38	28	64	109	0.57
3	19	22	44	32	72	124	0.90
4	22	25	50	37	74	134	1.33
6	25	30	57	40	94	163	1.98

