




MP




LINGATEC SOLUÇÃO EM MOVIMENTAÇÃO DE CARGAS LTDA
 Rua Danilo Valbuza, 600 - Laranjeiras - CAIEIRAS/SP - CEP: 07747-300
 11-4441-5420 - vendas@lingatec.com.br - www.lingatec.com.br

Green Pin® Pear Shaped Link EN 1677-4 GR8

Grade 8 pear shaped link EN 1677-4

- **Material:** alloy steel, grade 8, quenched and tempered
- **Safety factor:** MBL equals 4 x WLL
- **Standard:** EN1677-1 and ASTM A952/952M
- **Finish:** painted yellow (J), red (R) or white
- **Temperature range:** -40 °C up to +200 °C
- **Certification:** 2.1 2.2 3.1 MTC^a MPI^b CE II B
- **Article code:** scan QR code to see article codes
- **Note:** specific load pins available for 5, 7 and 9 mm hoist chain on request, which can be combined with respectively GPMP6, GPMP7/8, GPMP10

Scan for
additional
product
details



for chain diameter	working load limit	length	diameter pin	width	length inside	width inside	length	width outside	weight each
mm	t	a mm	b mm	c mm	d mm	e mm	f mm	g mm	kg
6	1.12	84	8	7	64	33	109	55	0.14
7/8	2	101	9	9	77	40	132	69	0.35
10	3.2	125	13	12	97	50	165	84	0.76
13	5.4	161	16	15	125	66	213	110	1.61
16	8.2	198	20	19	154	84	262	140	3.05
18/20	12.8	253	24	23	198	104	331	166	4.28