




MS



LINGATEC SOLUÇÃO EM MOVIMENTAÇÃO DE CARGAS LTDA
 Rua Danilo Valbuza, 600 - Laranjeiras - CAIEIRAS/SP - CEP: 07747-300
 11-4441-5420 - vendas@lingatec.com.br - www.lingatec.com.br

Green Pin® Master Link EN 1677-4 GR8

Grade 8 master link EN 1677-4

- **Material:** alloy steel, grade 8, quenched and tempered
- **Safety factor:** MBL equals 4 x WLL
- **Standard:** EN 1677-4, ASTM A952/952M and ASME B30.9
- **Finish:** painted white*
- **Temperature range:** -40 °C up to +200 °C
- **Certification:** 2.1 2.2 3.1 MTC[®] MPI[®] CE IIB
- **Article code:** scan QR code to see article codes
- **Note:** from 50 t without flat part

Scan for
additional
product
details



diameter	diameter chain 1 leg	diameter chain 2 legs		working load limit	length inside	width inside	thickness	weight each
a mm	mm	$\beta \leq 45^\circ$ mm	$45^\circ < \beta \leq 60^\circ$ mm	t	b mm	c mm	d mm	kg
13	6/7	6	6/7	1.6	115	60	7	0.40
16	8	7/8	8	3.2	120	70	7	0.60
18	10	10	10	4.5	135	75	9	0.84
20	13	-	13	6.2	150	82	11	1.10
22	16	13	16	8.2	170	90	14	1.60
25	18	-	18	10.6	190	103	14	2.30
28	20	16	19	12.8	209	120	17	3.10
30	20/22	18	20/22	15.5	235	125	17	4
36	-	19/20	-	20	270	145	22	6.60
38	26	22	26	25	250	150	22	7.10
45	32	26	32	37	300	200	22	12.1
50	-	32	-	50	380	200	-	18
55	-	-	-	63	360	200	-	21
70	-	-	-	100	500	250	-	44
80	-	-	-	125	503	280	-	60.7