



LINGATEC SOLUÇÃO EM MOVIMENTAÇÃO DE CARGAS LTDA
 Rua Danilo Valbuza, 600 - Laranjeiras - CAIEIRAS/SP - CEP: 07747-300
 11-4441-5420 - vendas@lingatec.com.br - www.lingatec.com.br



Green Pin® Master Link S/S-GR5



Grade 5 stainless steel master link

- **Material:** Duplex 1.4462, grade 5
- **Safety factor:** MBL equals 4 x WLL
- **Finish:** blasted
- **Temperature range:** -40 °C up to +200 °C
- **Certification:** 2.1 2.2 3.1 MTC® CE IIB
- **Article code:** scan QR code to see article codes

Scan for
additional
product
details



MSI



diameter	diameter chain 1 leg	diameter chain 2 legs		working load limit	length inside	width inside	thickness	weight each
a mm	mm	$\beta \leq 45^\circ$ mm	$45^\circ < \beta \leq 60^\circ$ mm	t	b mm	c mm	d mm	kg
13	6	-	6	1	110	60	6.5	0.34
16	8	6	8	1.25	110	60	6.5	0.53
18	10	8	10	2	135	75	8.5	0.82
22	13	10	13	3.2	160	90	10.5	1.45
26	16	13	16	5	180	100	13	2.29

CAD