



LINGATEC SOLUÇÃO EM MOVIMENTAÇÃO DE CARGAS LTDA
 Rua Danilo Valbuza, 600 - Laranjeiras - CAIEIRAS/SP - CEP: 07747-300
 11-4441-5420 - vendas@lingatec.com.br - www.lingatec.com.br




Green Pin® Locking Clamp ROV Shackle



Release ROV shackle (grade 8) with locking clamp

- **Material:** bow and pin alloy steel, grade 8, polar quality, quenched and tempered
- **Safety Factor:** MBL equals 6 x WLL
for shackles with WLL 120 t and up the MBL equals 5x WLL
- **Finish:** body painted white, pin painted green
- **Temperature Range:** -60 °C up to +200 °C (-40 °C up to +200 °C for WLL 120 t and up)
- **Certification:** 2.1 2.2 3.1 MTC^a MTC^b * LROS * CE IIA
- **Article code:** scan QR code to see article codes
- **Note:** supplied without wires; design your own wiring plan

Scan for
additional
product
details



P-5365



working load limit	diameter bow	diameter pin	diameter eye	width eye	width inside	length inside	width bow	length	length bolt	width	width locking clamp	weight pin	weight each
t	a mm	b mm	c mm	d mm	e mm	f mm	g mm	h mm	i mm	j mm	k mm	kg	kg
6.5	22	25	52	22	36	83	58	164	140	102	45	0.9	2.17
9.5	28	32	66	28	47	108	75	200	172	131	48	1.6	4.25
12	32	35	72	32	51	115	83	213	184	147	48	1.9	5.36
17	38	42	88	38	60	146	99	266	209	175	48	3.4	9.27
25	45	50	103	45	74	178	126	309	243	216	48	5	14.6
35	50	57	116	50	83	197	138	350	269	238	48	6.5	20.7
42.5	57	65	130	57	95	222	160	377	301	274	48	10.2	28.3
55	65	70	145	65	105	260	180	440	329	310	48	12	41
85	75	83	162	75	127	329	190	527	375	340	48	17.5	61
120	95	95	208	91	147	400	238	647	440	428	60	29.6	110
150	105	108	238	102	169	410	275	688	490	485	60	38.6	160
200	120	130	279	113	179	513	290	838	520	530	60	60.6	235
250	130	140	299	118	205	554	305	904	560	565	60	74.9	285

* For shackles ≥ WLL 150 t