




LINGATEC SOLUÇÃO EM MOVIMENTAÇÃO DE CARGAS LTDA
 Rua Danilo Valbuza, 600 - Laranjeiras - CAIEIRAS/SP - CEP: 07747-300
 11-4441-5420 - vendas@lingatec.com.br - www.lingatec.com.br



Green Pin® Spring Release ROV Shackle

Release ROV shackle (grade 8) with spring



Scan for
additional
product
details



P-5367

- **Material:** bow and pin alloy steel, grade 8, polar quality, quenched and tempered
- **Safety factor:** MBL equals 5 x WLL
- **Finish:** body painted white, pin painted green
- **Temperature Range:** -40 °C up to +200 °C
- **Certification:** 2.1 2.2 3.1 MTC^a MTC^b * LROS * CE IIA
- **Article code:** scan QR code to see article codes
- **Note:** for in-line use only.

this shackle is assembled with wire rope slings and monkey's fist. For size starting from WLL 42.5 t up to and including 150 t a special compression tool (sold separately) is required to assemble the shackle.



working load limit	diameter bow	diameter pin	diameter eye	width eye	width inside	length inside	width bow	length	length bolt	width	weight pin	weight each
t	a mm	b mm	c mm	d mm	e mm	f mm	g mm	h mm	i mm	j mm	kg	kg
12	32	35	72	32	51	115	83	201	291	147	2	5.24
13.5	35	38	80	35	57	133	92	227	301	162	2.4	7
17	38	42	88	38	60	146	99	249	360	175	3.5	9.25
25	45	50	103	45	74	178	126	300	370	216	5.2	15.5
35	50	57	116	50	83	197	138	334	400	238	7.1	20.4
42.5	57	65	130	57	95	222	160	377	460	274	11.3	39
55	65	70	145	65	105	260	180	433	490	310	13.8	42
85	75	83	162	75	127	329	190	527	587	340	23.3	67
120	95	95	208	91	147	399	238	646	687	428	37.4	123
150	105	108	238	102	169	410	275	688	727	485	49.2	168

For shackles $\geq$ WLL 150 t