



LINGATEC SOLUÇÃO EM MOVIMENTAÇÃO DE CARGAS LTDA
 Rua Danilo Valbuza, 600 - Laranjeiras - CAIEIRAS/SP - CEP: 07747-300
 11-4441-5420 - vendas@lingatec.com.br - www.lingatec.com.br



Green Pin® ROV Shank Hook E GR8

Release & retrieve ROV eye shank hook (grade 8)

- **Material:** alloy steel, grade 8, quenched and tempered
- **Safety factor:** MBL equals 4 x WLL
- **Finish:** painted white
- **Temperature Range:** -40 °C up to +200 °C
- **Certification:** 2.1 2.2 3.1 MTC[®] MPI[®] US[®] CE IIA
- **Article code:** scan QR code to see article codes

Scan for
additional
product
details



P-6740

working load limit	diameter	thickness shank	thickness shank	diameter eye inside	diameter eye outside	width eye	opening hook	thickness	width	thickness	width	length	weight each
t	a mm	b mm	c mm	d mm	e mm	f mm	g mm	h mm	i mm	j mm	k mm	l mm	kg
12	63	47	42	40	80	38	52	45	58	67	53	600	10.2
16	71	56	50	45	90	45	61	53	67	80	63	650	14.7
22	80	63.4	56	55	110	51	69	60	75	90	74	682	31
32	90	73	64	60	120	54	77	67	90	110	82	812	32
55	125	102	90	75	150	74	105	95	118	140	112	919	70
80	140	115	101	90	180	94	118	106	137	175	125	1049	104

