




LINGATEC SOLUÇÃO EM MOVIMENTAÇÃO DE CARGAS LTDA
 Rua Danilo Valbuza, 600 - Laranjeiras - CAIEIRAS/SP - CEP: 07747-300
 11-4441-5420 - vendas@lingatec.com.br - www.lingatec.com.br



TRIPLE SWIVEL RING

METRIC THREADS



1 in = 25.4 mm

Reference	Diameter	SF 5:1 WLL (t)	Standard L ₁ (mm)	Torque (Nm)		S ₁ (mm)	S ₂ (mm)	A (mm)	B (mm)	C (mm)	D (mm)	E (mm)	F (mm)	G (mm)	H (mm)	Weight	
																(kg)	(lbs)
TSR M 8	M 8 (x1,25)	0,40	15	6	18	8	16	33	56	30	41	25	10	58	9,5	0,4	0.88
TSR M 10	M 10 (x1,50)	0,70	18	10	18	8	16	33	56	30	41	25	10	58	9,5	0,4	0.88
TSR M 12	M 12 (x1,75)	1,05	21	15	18	8	16	33	56	30	41	25	10	58	9,5	0,4	0.88
TSR M 14	M 14 (x2)	1,40	23	30	24	8	20	45	81	45	48	34	16	79	13,0	1,1	2.43
TSR M 16	M 16 (x2)	2,00	27	50	24	8	20	45	81	45	48	34	16	79	13,0	1,2	2.65
TSR M 18	M 18 (x2,5)	2,30	27	70	24	8	20	45	81	45	48	34	16	79	13,0	1,2	2.65
TSR M 20	M 20 (x2,5)	2,50	30	100	24	8	20	45	81	45	48	34	16	79	13,0	1,2	2.65
TSR M 22*	M 22 (x2,5)	3,00	33	120	45	14	24	62	105	60	80	45	20	106	19,0	2,8	6.17
TSR M 24*	M 24 (x3)	4,00	36	160	45	14	24	62	105	60	80	45	20	106	19,0	2,9	6.39
TSR M 27*	M 27 (x3)	5,00	36	200	45	14	24	62	105	60	80	45	20	106	19,0	2,9	6.39
TSR M 30*	M 30 (x3,5)	6,30	45	250	45	14	24	62	105	60	80	45	20	106	19,0	3,0	6.61
TSR M 36*	M 36 (x4)	10,00	54	320	54	19	30	81	140	80	111	71	30	148	26,5	7,6	16.76
TSR M 42*	M 42 (x4,5)	12,50	63	400	58	19	30	84	146	80	111	71	30	148	26,5	7,8	17.20

Reference	Diameter	SF 4:1 WLL (t)	Standard L ₁ (mm)	Torque (Nm)		S ₁ (mm)	S ₂ (mm)	A (mm)	B (mm)	C (mm)	D (mm)	E (mm)	F (mm)	G (mm)	H (mm)	Weight	
																(kg)	(lbs)
TSR M 48	M 48 (x5)	20,00	68	600	69	19	30	100	178	110	135	90	42	180	33,0	17,5	38.58
TSR M 56	M 56 (x5,5)	22,00	78	600	73	19	30	104	184	110	135	90	42	190	33,0	18,0	39.68

* On request / Sur demande / Auf Anfrage / Bajo solicitud

11.2024

70