




UCFO



LINGATEC SOLUÇÃO EM MOVIMENTAÇÃO DE CARGAS LTDA
 Rua Danilo Valbuza, 600 - Laranjeiras - CAIEIRAS/SP - CEP: 07747-300
 11-4441-5420 - vendas@lingatec.com.br - www.lingatec.com.br

Green Pin® Foundry Hook E GR10

Grade 100 eye foundry hook

- **Material:** alloy steel, grade 100, quenched and tempered
- **Safety factor:** MBL equals 4 x WLL
- **Standard:** ASTM A952/A952M-02
- **Finish:** painted blue
- **Temperature range:** -40°F up to +392°F (-40°C up to +200°C)
- **Certification:** 2.1 2.2 3.1 MPI® DGUV

partnumber	for chain diameter	working load limit	length	diameter eye inside	width opening	thickness	width	diameter eye outside	width outside	length	thickness	weight each
	inch	t	a inch	b inch	c inch	d inch	e inch	f inch	g inch	h inch	i inch	lbs
GPUCFO6	$\frac{7}{32}$	1.4	$3\frac{21}{32}$	$\frac{23}{32}$	$1\frac{7}{8}$	$\frac{21}{32}$	$\frac{7}{8}$	$1\frac{1}{2}$	$3\frac{13}{16}$	$4\frac{7}{8}$	$\frac{1}{4}$	0.73
GPUCFO8	$\frac{9}{32} - \frac{5}{16}$	2.6	$4\frac{7}{8}$	$\frac{31}{32}$	$2\frac{15}{32}$	$\frac{7}{8}$	$1\frac{5}{32}$	$1\frac{31}{32}$	$5\frac{3}{32}$	$6\frac{1}{2}$	$\frac{5}{16}$	1.72
GPUCFO10	$\frac{3}{8}$	4	$6\frac{3}{16}$	$1\frac{5}{16}$	$3\frac{5}{32}$	$1\frac{3}{32}$	$1\frac{13}{32}$	$2\frac{9}{16}$	$6\frac{11}{32}$	$8\frac{3}{16}$	$\frac{13}{32}$	3.31
GPUCFO13	$\frac{1}{2}$	6.8	$7\frac{15}{32}$	$1\frac{23}{32}$	$3\frac{25}{32}$	$1\frac{13}{32}$	$1\frac{13}{16}$	$3\frac{5}{16}$	$7\frac{25}{32}$	$10\frac{3}{32}$	$\frac{1}{2}$	6.61

In mm

partnumber	for chain diameter	working load limit	length	diameter eye inside	width opening	thickness	width	diameter eye outside	width outside	length	thickness	weight each
	mm	t	a mm	b mm	c mm	d mm	e mm	f mm	g mm	h mm	i mm	kg
GPUCFO6	6	1.4	93	18	48	17	22	38	97	124	6	0.33
GPUCFO8	8	2.6	124	25	63	22	29	50	129	165	8	0.78
GPUCFO10	10	4	157	33	80	28	36	65	161	208	10	1.5
GPUCFO13	13	6.8	190	44	96	36	46	84	198	256	13	3

CAD