




UCRCT



LINGATEC SOLUÇÃO EM MOVIMENTAÇÃO DE CARGAS LTDA
 Rua Danilo Valbuza, 600 - Laranjeiras - CAIEIRAS/SP - CEP: 07747-300
 11-4441-5420 - vendas@lingatec.com.br - www.lingatec.com.br

Green Pin Tycan® Grab Hook CL GR10

Grade 10 clevis grab hook

- **Material:** alloy steel, grade 10, quenched and tempered
- **Safety factor:** MBL equals 4 x WLL and MBL equals 2 x Lashing Capacity
- **Standard:** follows the EN1677 with grade 10 values and conforms to ASTM A952/A952M
- **Finish:** painted blue
- **Temperature range:** -40 °C up to +200 °C
- **Certification:** 2.1 2.2 3.1 MTC[®] MPI[®] CE IIB
- **Article code:** scan QR code to see article codes
- **Note:** GPUCRCT25 and GPUCRCT30 can also be directly connected with Green Pin Tycan® loadbinder (P-7180)

Scan for
additional
product
details



for chain size	lashing capacity	length	width	width outside	opening	thickness	width	width outside	length outside	diameter pin	weight each
mm	t	a mm	b mm	c mm	d mm	e mm	f mm	g mm	h mm	i mm	kg
15x25	10	102	24	68	25	16	40	99	178	20	2.12
13x30	13.6	100	32	74	30	20	40	102	177	20	1.94
15x40	20.6	128	42	96	40	24	44.7	127	216.5	24	3.37

CAD INFO