




UCSC



**LINGATEC SOLUÇÃO EM MOVIMENTAÇÃO DE CARGAS LTDA**  
 Rua Danilo Valbuza, 600 - Laranjeiras - CAIEIRAS/SP - CEP: 07747-300  
 11-4441-5420 - vendas@lingatec.com.br - www.lingatec.com.br

## Green Pin® Sling Hook CL GR10

### Grade 10 clevis sling hook

- **Material:** alloy steel, grade 10, quenched and tempered
- **Safety factor:** MBL equals 4 x WLL
- **Standard:** follows the EN1677 with grade 10 values and conforms to ASTM A952/A952M
- **Finish:** painted blue
- **Temperature range:** -40 °C up to +200 °C
- **Certification:** 2.1 2.2 3.1 MTC<sup>+</sup> MPI<sup>+</sup> DGUV CE IIIB
- **Article code:** scan QR code to see article codes

Scan for  
additional  
product  
details



| for chain<br>diameter | working<br>load<br>limit | length  | width   | width<br>opening | thickness | width   | width<br>outside | width<br>outside | length<br>outside | diameter<br>pin | weight<br>each |
|-----------------------|--------------------------|---------|---------|------------------|-----------|---------|------------------|------------------|-------------------|-----------------|----------------|
| mm                    | t                        | a<br>mm | b<br>mm | c<br>mm          | d<br>mm   | e<br>mm | f<br>mm          | g<br>mm          | h<br>mm           | i<br>mm         | kg             |
| 6                     | 1.4                      | 74      | 7       | 26               | 15        | 20      | 28               | 72               | 108               | 8               | 0.29           |
| 7                     | 1.95                     | 95      | 9       | 30               | 20        | 24      | 32               | 87               | 136               | 9               | 0.58           |
| 8                     | 2.6                      | 95      | 9       | 30               | 20        | 24      | 32               | 87               | 136               | 9               | 0.58           |
| 10                    | 4                        | 113     | 11      | 33               | 24        | 29      | 42               | 106              | 164               | 13              | 1.11           |
| 13                    | 6.8                      | 139     | 15      | 37               | 32        | 39      | 54               | 133              | 208               | 16              | 2.12           |
| 16                    | 10.3                     | 162     | 18      | 44               | 40        | 44      | 68               | 165              | 240               | 20              | 3.78           |
| 20                    | 16                       | 199     | 23      | 61               | 49        | 62      | 82               | 208              | 305               | 24              | 7.49           |