




UCSO



LINGATEC SOLUÇÃO EM MOVIMENTAÇÃO DE CARGAS LTDA
 Rua Danilo Valbuza, 600 - Laranjeiras - CAIEIRAS/SP - CEP: 07747-300
 11-4441-5420 - vendas@lingatec.com.br - www.lingatec.com.br

Green Pin® Sling Hook E GR10

Grade 10 eye sling hook

- **Material:** alloy steel, grade 10, quenched and tempered
- **Safety factor:** MBL equals 4 x WLL
- **Standard:** follows the EN1677 with grade 10 values and conforms to ASTM A952/A952M
- **Finish:** painted blue
- **Temperature range:** -40 °C up to +200 °C
- **Certification:** 2.1 2.2 3.1 MTC[®] MPI[®] DGVV CE IIB
- **Article code:** scan QR code to see article codes
- **Note:** from 10 t without flat part

Scan for
additional
product
details



for chain diameter	working load limit	length	diameter inside eye	width opening	thickness	width	diameter eye outside	width outside	length	width	thickness	weight each
mm	t	a mm	b mm	c mm	d mm	e mm	f mm	g mm	h mm	i mm	j mm	kg
6	1.4	86	23	26	15	19	43	73	114	10	6	0.28
7/8	2.6	103	26	30	19	24	51	87	139	12	8	0.52
10	4	129	36	33	24	28	65	106	171	15	10	1.09
13	6.8	152	41	37	32	39	77	133	209	18	12	1.94
16	10.3	191	52	43	40	43	94	165	255	21	17	3.51
20	16	237	61	61	49	61	115	208	326	28	21	7.08