




**LINGATEC SOLUÇÃO EM MOVIMENTAÇÃO DE CARGAS LTDA**  
Rua Danilo Valbuza, 600 - Laranjeiras - CAIEIRAS/SP - CEP: 07747-300  
11-4441-5420 - vendas@lingatec.com.br - www.lingatec.com.br




## Green Pin® Shortening Clutch with Lock GR10

### Grade 10 shortening clutch with locking pin

Scan for  
additional  
product  
details



UGCV



- **Material:** alloy steel, grade 10, quenched and tempered
- **Safety factor:** MBL equals 4 x WLL
- **Standard:** follows the EN1677 and DIN5692 with grade 10 values and ASTM A952/A952M
- **Finish:** painted blue
- **Temperature range:** -40 °C up to +200 °C
- **Certification:** 2.1 2.2 3.1 MTC<sup>a</sup> MPI<sup>b</sup> DGUV CE IIB
- **Article code:** scan QR code to see article codes

| for chain<br>diameter | working<br>load<br>limit | length  | width<br>inside | length  | width<br>outside | width   | diameter<br>pin | diameter<br>pin | weight<br>each |
|-----------------------|--------------------------|---------|-----------------|---------|------------------|---------|-----------------|-----------------|----------------|
| mm                    | t                        | a<br>mm | b<br>mm         | c<br>mm | d<br>mm          | e<br>mm | f<br>mm         | g<br>mm         | kg             |
| 6                     | 1.4                      | 52      | 23              | 75      | 42               | 7       | 8               | 7               | 0.23           |
| 8                     | 2.6                      | 67      | 30              | 94      | 50               | 9       | 10              | 8               | 0.44           |
| 10                    | 4                        | 83      | 38              | 116     | 63               | 11      | 13              | 12              | 0.87           |
| 13                    | 6.8                      | 104     | 49              | 149     | 79               | 14      | 16              | 16              | 1.67           |
| 16                    | 10.3                     | 127     | 60              | 184     | 99               | 18      | 20              | 20              | 3.10           |
| 20                    | 16                       | 154     | 75              | 215     | 124              | 22      | 24              | 20              | 5.80           |