





LINGATEC SOLUÇÃO EM MOVIMENTAÇÃO DE CARGAS LTDA
Rua Danilo Valbuza, 600 - Laranjeiras - CAIEIRAS/SP - CEP: 07747-300
11-4441-5420 - vendas@lingatec.com.br - www.lingatec.com.br



UMJ



Green Pin® Connecting Link GR10

Grade 10 connecting link

- **Material:** alloy steel, grade 10, quenched and tempered
- **Safety factor:** MBL equals 4 x WLL
- **Standard:** follows the EN1677 with grade 10 values and conforms to ASTM A952/A952M
- **Finish:** painted blue
- **Temperature range:** -40 °C up to +200 °C
- **Certification:** 2.1 2.2 3.1 MTC^a MPI^b DGUV CE IIB
- **Article code:** scan QR code to see article codes

Scan for
additional
product
details



for chain diameter	working load limit	diameter	width outside	width inside	length inside	length inside	diameter eye	width inside	weight each
mm	t	a mm	b mm	c mm	d mm	e mm	f mm	g mm	kg
6	1.4	8	42	11	20	52	11	15	0.09
7	1.95	9	53	14	20	55	16	19	0.18
8	2.6	9	53	14	20	55	16	19	0.18
10	4	12	66	18	23	64	18	23	0.31
13	6.8	16	83	21	32	85	24	28	0.68
16	10.3	19	105	25	40	105	28	34	1.27
20	16	23	122	33	49	128	38	42	2.27

CAD INFO