




UMP



LINGATEC SOLUÇÃO EM MOVIMENTAÇÃO DE CARGAS LTDA
 Rua Danilo Valbuza, 600 - Laranjeiras - CAIEIRAS/SP - CEP: 07747-300
 11-4441-5420 - vendas@lingatec.com.br - www.lingatec.com.br

Green Pin® Pear Shaped Link GR10

Grade 10 pear shaped link

- **Material:** alloy steel, grade 10, quenched and tempered
- **Safety factor:** MBL equals 4 x WLL
- **Standard:** follows the EN1677 with grade 10 values and conforms to ASTM A952/A952M
- **Finish:** painted blue
- **Temperature range:** -40 °C up to +200 °C
- **Certification:** 2.1 2.2 3.1 MTC² MPI² CE IIB
- **Article code:** scan QR code to see article codes

Scan for
additional
product
details



for chain diameter	working load limit	length	diameter pin	width	length inside	width inside	length	width outside	weight each
mm	t	a mm	b mm	c mm	d mm	e mm	f mm	g mm	kg
6	1.4	84	8	7	64	33	109	55	0.14
7	1.95	100	10	9	77	40	132	69	0.28
8	2.6	100	10	9	77	40	132	69	0.28
10	4	125	13	12	97	50	165	84	0.63
13	6.8	161	16	15	125	66	213	110	1.40
16	10.3	198	20	19	154	84	262	140	2.73

CAD INFO