





UMS



LINGATEC SOLUÇÃO EM MOVIMENTAÇÃO DE CARGAS LTDA
 Rua Danilo Valbuza, 600 - Laranjeiras - CAIEIRAS/SP - CEP: 07747-300
 11-4441-5420 - vendas@lingatec.com.br - www.lingatec.com.br

Green Pin® Master Link GR10

Grade 10 master link

- **Material:** alloy steel, grade 10, quenched and tempered
- **Safety factor:** MBL equals 4 x WLL
- **Standard:** follows the EN1677 with values for grade 10 and conforms to ASTM A952/A952M and ASME B30.9
- **Finish:** painted blue
- **Temperature range:** -40 °C up to +200 °C
- **Certification:** 2.1 2.2 3.1 MTC^b MPI^a CE IIB
- **Article code:** scan QR code to see article codes
- **Note:** for use of this component in a wire rope sling the safety factor must be 5 : 1, see the table on page 84

Scan for
additional
product
details



diameter	diameter chain 1 leg	diameter chain 2 legs		working load limit	length inside	width inside	thickness	weight each
a mm	mm	$\beta \leq 45^\circ$ mm	$45^\circ < \beta \leq 60^\circ$ mm	t	b mm	c mm	d mm	kg
13	6	6	6	2	115	60	7	0.40
16	8	-	8	3.2	120	70	7	0.60
18	10	8	10	5.4	135	75	9	0.84
22	13	10	13	8.2	170	90	11	1.60
25	16	13	16	11.2	190	103	14	2.17
30	18/20	16	18/20	16	235	125	17	4
38	22	20/22	22	27.6	250	150	22	7.10