



LINGATEC SOLUÇÃO EM MOVIMENTAÇÃO DE CARGAS LTDA
Rua Danilo Valbuza, 600 - Laranjeiras - CAIEIRAS/SP - CEP: 07747-300
11-4441-5420 - vendas@lingatec.com.br - www.lingatec.com.br



Green Pin® Master Link Assembly GR10

Grade 10 master link assembly



Scan for
additional
product
details



- **Material:** alloy steel, grade 10, quenched and tempered
- **Safety factor:** MBL equals 4 x WLL
- **Standard:** follows the EN1677 with values for grade 10 and conforms to ASTM A952/A952M and ASME B30.9
- **Finish:** painted blue
- **Temperature range:** -40 °C up to +200 °C
- **Certification:** 2.1 2.2 3.1 MTC^b MPI^a CE IIB
- **Article code:** scan QR code to see article codes
- **Note:** for use of this component in a wire rope sling the safety factor must be 5 : 1, see the table on page 84



UMTS



diameter	diameter chain 3/4 legs		working load limit	length inside	width inside	diameter	length inside	width inside	thickness	weight each
a mm	$\beta \leq 45^\circ$ mm	$45^\circ < \beta \leq 60^\circ$ mm	t	b mm	c mm	d mm	e mm	f mm	g mm	kg
18	6	6	3.65	135	75	16	120	70	7	1.97
22	8	8/10	6.8	170	90	18	135	75	9	3.30
28	10	13	11	209	120	20	150	82	11	5.40
36	13	16	17.7	270	145	25	190	103	14	11.2
38	16	18/19	21.2	250	150	30	235	125	17	15.1
50	20	22	41.6	380	200	38	250	150	22	32.2

CAD