



LINGATEC SOLUÇÃO EM MOVIMENTAÇÃO DE CARGAS LTDA
Rua Danilo Valbuza, 600 - Laranjeiras - CAIEIRAS/SP - CEP: 07747-300
11-4441-5420 - vendas@lingatec.com.br - www.lingatec.com.br



Green Pin® Wider Master Link Assembly GR10



Grade 10 wider master link assembly

- **Material:** alloy steel, grade 10, quenched and tempered
- **Safety factor:** MBL equals 5 x WLL
- **Standard:** follows the EN1677 with values for grade 10 and conforms to ASTM A952/A952M and ASME B30.9
- **Finish:** painted blue
- **Temperature range:** -40 °C up to +200 °C
- **Certification:** 2.1 2.2 3.1 MTC^b MPI^a CE IIB
- **Article code:** scan QR code to see article codes

Scan for
additional
product
details



UMTSW



working load limit	diameter	length inside	width inside	diameter	length inside	width inside	thickness	weight each
t	a mm	b mm	c mm	d mm	e mm	f mm	g mm	kg
4.3	19	160	90	14	120	70	9	1.96
6.7	23	180	100	17	160	90	9	3.50
28.1	40	300	160	33	270	140	17	19.8
38.3	45	340	180	38	275	150	21	27.8
75	60	400	200	50	380	200	50	62.5

CAD