




UXLC



LINGATEC SOLUÇÃO EM MOVIMENTAÇÃO DE CARGAS LTDA
 Rua Danilo Valbuza, 600 - Laranjeiras - CAIEIRAS/SP - CEP: 07747-300
 11-4441-5420 - vendas@lingatec.com.br - www.lingatec.com.br

Green Pin® Self Locking Hook CL GR10

Grade 10 clevis self locking hook

- **Material:** alloy steel, grade 10, quenched and tempered
- **Safety factor:** MBL equals 4 x WLL
- **Standard:** follows the EN1677 with grade 10 values and conforms to ASTM A952/A952M
- **Finish:** painted blue
- **Temperature range:** -40 °C up to +200 °C
- **Certification:** 2.1 2.2 3.1 MTC² MPI² DGUV CE IIB
- **Article code:** scan QR code to see article codes

Scan for
additional
product
details



for chain diameter	working load limit	length	width	width opening	thickness	width	width outside	width outside	length	diameter pin	weight each
mm	t	a mm	b mm	c mm	d mm	e mm	f mm	g mm	h mm	i mm	kg
6	1.4	93	7	32	17	24	28	75	130	8	0.49
7	1.95	116	9	43	24	28	32	91	161	10	0.91
8	2.6	116	9	43	24	28	32	91	161	10	0.91
10	4	144	11	48	32	34	42	112	201	13	1.74
13	6.8	169	15	63	37	44	54	141	242	16	3.33
16	10.3	204	18	75	43	56	68	182	296	20	6.75
20	16	234	22	90	52	62	82	205	341	24	9.57