




**LINGATEC SOLUÇÃO EM MOVIMENTAÇÃO DE CARGAS LTDA**  
Rua Danilo Valbuza, 600 - Laranjeiras - CAIEIRAS/SP - CEP: 07747-300  
11-4441-5420 - vendas@lingatec.com.br - www.lingatec.com.br



UXLO



## Green Pin® Self Locking Hook E GR10

### Grade 10 eye self locking hook

- **Material:** alloy steel, grade 10, quenched and tempered
- **Safety factor:** MBL equals 4 x WLL
- **Standard:** follows the EN1677 with grade 10 values and conforms to ASTM A952/A952M
- **Finish:** painted blue
- **Temperature range:** -40 °C up to +200 °C
- **Certification:** 2.1 2.2 3.1 MTC<sup>a</sup> MPI<sup>b</sup> DGUV CE IIB
- **Article code:** scan QR code to see article codes

Scan for  
additional  
product  
details



| for chain<br>diameter | working<br>load<br>limit | length  | diameter<br>inside<br>eye | width<br>opening | thickness | width   | width<br>outside | width<br>outside | length  | width   | thickness | weight<br>each |
|-----------------------|--------------------------|---------|---------------------------|------------------|-----------|---------|------------------|------------------|---------|---------|-----------|----------------|
| mm                    | t                        | a<br>mm | b<br>mm                   | c<br>mm          | d<br>mm   | e<br>mm | f<br>mm          | g<br>mm          | h<br>mm | i<br>mm | j<br>mm   | kg             |
| 6                     | 1.4                      | 113     | 24                        | 32               | 16        | 24      | 47               | 75               | 148     | 11      | 6         | 0.51           |
| 7/8                   | 2.6                      | 136     | 30                        | 43               | 24        | 28      | 57               | 91               | 178     | 14      | 8         | 0.91           |
| 10                    | 4                        | 168     | 36                        | 48               | 32        | 34      | 68               | 110              | 218     | 16      | 10        | 1.79           |
| 13                    | 6.8                      | 201     | 47                        | 63               | 37        | 43      | 87               | 141              | 264     | 20      | 13        | 3.36           |
| 16                    | 10.3                     | 251     | 60                        | 75               | 43        | 56      | 111              | 182              | 332     | 26      | 16        | 7              |
| 20                    | 16                       | 283     | 70                        | 90               | 52        | 62      | 126              | 203              | 373     | 28      | 21        | 9.22           |

CAD INFO