



LINGATEC SOLUÇÃO EM MOVIMENTAÇÃO DE CARGAS LTDA
Rua Danilo Valbuza, 600 - Laranjeiras - CAIEIRAS/SP - CEP: 07747-300
11-4441-5420 - vendas@lingatec.com.br - www.lingatec.com.br



Green Pin® Self Locking Hook E RT GR10


Grade 10 eye self locking hook with recessed trigger

- **Material:** alloy steel, grade 10, quenched and tempered
- **Safety factor:** MBL equals 4 x WLL
- **Standard:** follows the EN1677 with grade 10 values and conforms to ASTM A952/A952M
- **Finish:** painted blue
- **Temperature range:** -40 °C up to +200 °C
- **Certification:** 2.1 2.2 3.1 MTC^a MPI^b DGVV CE IIB
- **Article code:** scan QR code to see article codes

Scan for
additional
product
details



UXLORT



for chain diameter	working load limit	length	diameter inside eye	width opening	thickness	width	width outside	width outside	length	width	thickness	weight each
mm	t	a mm	b mm	c mm	d mm	e mm	f mm	g mm	h mm	i mm	j mm	kg
7/8	2.6	136	30	43	24	28	57	91	178	14	7	0.90
10	4	168	36	48	32	34	68	111	218	16	10	1.77
13	6.8	201	47	63	37	43	87	141	264	20	13	3.34
16	10.3	251	60	75	43	56	111	182	332	26	16	6.98
20	16	283	70	90	52	62	126	203	373	28	20	9.20

CAD INFO