



LINGATEC SOLUÇÃO EM MOVIMENTAÇÃO DE CARGAS LTDA
 Rua Danilo Valbuza, 600 - Laranjeiras - CAIEIRAS/SP - CEP: 07747-300
 11-4441-5420 - vendas@lingatec.com.br - www.lingatec.com.br




Green Pin® Self Locking Hook SCL EN 1677-3 GR8

Grade 8 swivel clevis self locking hook EN 1677-3

Scan for
additional
product
details



XLBA



- **Material:** alloy steel, grade 8, quenched and tempered
- **Safety factor:** MBL equals 4 x WLL
- **Standard:** EN1677-3 and ASTM A952/A952M
- **Finish:** painted red (R) or white
- **Temperature range:** -40 °C up to +200 °C
- **Certification:** 2.1 2.2 3.1 MTC^a MPI^b DGUV CE IIB
- **Article code:** scan QR code to see article codes
- **Note:** specific load pins available for 5, 7 and 9 mm hoist chain on request, which can be combined with respectively GPXLBA0, GPXLBA1, GPXLBA2

for chain diameter	working load limit	length	width	width opening	thickness	width	width outside	width outside	length	diameter pin	weight each
mm	t	a mm	b mm	c mm	d mm	e mm	f mm	g mm	h mm	i mm	kg
6	1.12	149	7	32	17	24	56	75	186	8	0.79
7/8	2	178	9	43	24	28	65	91	223	9	1.37
10	3.2	218	12	48	32	34	79	112	274	13	2.6
13	5.4	250	15	63	37	44	96	141	324	16	4.72
16	8.2	322	19	75	43	56	121	182	414	20	9.80

CAD INFO