




LINGATEC SOLUÇÃO EM MOVIMENTAÇÃO DE CARGAS LTDA
Rua Danilo Valbuza, 600 - Laranjeiras - CAIEIRAS/SP - CEP: 07747-300
11-4441-5420 - vendas@lingatec.com.br - www.lingatec.com.br



XLC



Green Pin® Self Locking Hook CL EN 1677-3 GR8

Grade 8 clevis self locking hook EN 1677-3

- **Material:** alloy steel, grade 8, quenched and tempered
- **Safety factor:** MBL equals 4 x WLL
- **Standard:** EN1677-3 and ASTM A952/A952M
- **Finish:** painted white*
- **Temperature range:** -40 °C up to +200 °C
- **Certification:** 2.1 2.2 3.1 MTC^a MPI^b DGUV CE IIB
- **Article code:** scan QR code to see article codes
- **Note:** specific load pins available for 5, 7 and 9 mm hoist chain on request, which can be combined with respectively GPXLC0, GPXLC1, GPXLC2

Scan for
additional
product
details



for chain diameter	working load limit	length	width	width opening	thickness	width	width outside	width outside	length	diameter pin	weight each
mm	t	a mm	b mm	c mm	d mm	e mm	f mm	g mm	h mm	i mm	kg
6	1.12	93	7	32	17	24	28	75	130	8	0.49
7/8	2	116	9	43	24	28	32	91	161	9	0.91
10	3.2	144	12	48	32	34	42	112	201	13	1.77
13	5.4	169	15	63	37	44	54	141	242	16	3.33
16	8.2	204	18	75	43	56	68	182	296	20	6.75
18/20	12.8	234	22	90	52	62	82	205	341	24	9.57