




XLE



LINGATEC SOLUÇÃO EM MOVIMENTAÇÃO DE CARGAS LTDA
 Rua Danilo Valbuza, 600 - Laranjeiras - CAIEIRAS/SP - CEP: 07747-300
 11-4441-5420 - vendas@lingatec.com.br - www.lingatec.com.br

Green Pin® Self Locking Hook SE EN 1677-3 GR8

Grade 8 swivel self locking hook EN 1677-3

- **Material:** alloy steel, grade 8, quenched and tempered
- **Safety factor:** MBL equals 4 x WLL
- **Standard:** EN1677-3 and ASTM A952/A952M
- **Finish:** painted white*
- **Temperature range:** -40 °C up to +200 °C
- **Certification:** 2.1 2.2 3.1 MTC[®] MPI[®] DGVV CE IIB
- **Article code:** scan QR code to see article codes
- **Note:** equipped with thrust needle roller bearing to enable rotation under load

Scan for
additional
product
details



for chain diameter	working load limit	length	length inside	width inside	width opening	thickness	width	width outside	length	diameter	thickness	weight each
mm	t	a mm	b mm	c mm	d mm	e mm	f mm	g mm	h mm	i mm	j mm	kg
5/6	1.12	123	33	32	32	16	24	75	191	12	6	0.78
7/8	2	149	41	37	43	24	28	91	232	14	8	1.39
10	3.2	186	47	48	48	32	34	112	283	16	11	2.56
13	5.4	214	60	58	63	37	44	141	337	21	14	4.56
16	8.2	273	67	73	75	43	56	182	420	25	17	9.50
18/20	12.8	304	87	82	90	52	62	205	478	25	22	12.7