
LINGATEC SOLUÇÃO EM MOVIMENTAÇÃO DE CARGAS LTDA
Rua Danilo Valbuza, 600 - Laranjeiras – CAIEIRAS/SP – CEP: 07747-300
11-4441-5420 - vendas@lingatec.com.br - www.lingatec.com.br


Green Pin® Lifting Clamp U-type

Universal plate clamp for lifting and transportation in all directions



P-6625





- **Material:** carbon and alloy steel
- **Safety factor:** MBL equals 5 x WLL
- **Standard:** generally to EN 13155, ASME B30.20-2010 and AS 4991
- **Finish:** painted
- **Temperature range:** -40°C up to +100°C
- **Certification:** 2.1 2.2 MTC a CE

type	working load limit	width opening	length opening	width	length	diameter inside eye	width	thickness	thickness	weight each
	t	a mm	b mm	c mm	d mm	e mm	f mm	g mm	h mm	kg
0.75 U	0.75	0-13	47	37	203	30	100	37	10	1.8
2 U	2	0-35	78	56	372	70	183	56	16	8
3 U	3	0-35	78	56	372	70	183	56	16	8
6 U	6	0-50	114	82	527	78	259	78	32	24
7.5 U	7.5	0-55	111	70	560	78	267	86	32	28
9 U	9	0-55	111	70	560	78	267	86	32	29
12 U	12	0-52	148	100	648	85	295	94	48	41

Certificates

Type 2.1	2.1	**Works certificate to EN 10204** Statement of compliance with the order.
Type 2.2	2.2	**Works certificate to EN 10204** Statement of compliance with the order, stating the results of non-specific inspection.
Type MTC a	MTC a	**Manufacturer test certificate** Statement of compliance with the order, stating the results of proof load testing samples of a production batch. Products are not individually tested.
Type CE	CE	**CE declaration of conformity** CE Declaration of Conformity in accordance with annex IIA of the machine directive 2006/42/EC and the latest amendments.